

Shower Controls without Piezo Button



SLZA 20



SLZA 20H



SLZA 20T

Characteristics:

- only for use with set of SLZA 01M/02M
- SLZA 20 - destined for premixed water
- SLZA 20H - destined for hot and cold water, temperature regulation by mixer
- SLZA 20T - destined for hot and cold water, temperature regulation by thermostatic mixer
- after paying the amount into coin machine and adjusted time delay water starts to flow from shower head
- shower time can not be interrupted
- material stainless steel AISI 304, brushed, material stainless steel AISI 316L could be made to order

Supply Specification:

- SLZA 20 - supply No. 88200 stainless steel cover with fitting
- SLZA 20H - supply No. 88205 and electromagnetic valve,
- SLZA 20T - supply No. 88206 ball valve and brass fittings

Technical Specification:

- Operating voltage: 24V DC
- Power input: 6,5 W

Shower Controls with Piezo Button



SLZA 20P



SLZA 20PH



SLZA 20PT

Characteristics:

- only for use with set of SLZA 01N/02N
- SLZA 20P - destined for premixed water
- SLZA 20PH - destined for hot and cold water, temperature regulation by mixer
- SLZA 20PT - destined for hot and cold water, temperature regulation by thermostatic mixer
- push piezo button to start water flowing
- with piezo button it is possible start and stop water in pre-paid time
- material stainless steel AISI 304, brushed, material stainless steel AISI 316L could be made to order

Supply Specification:

- SLZA 20P - supply No. 88207 stainless steel cover with piezo
- SLZA 20PH - supply No. 88208 button and fitting and
- SLZA 20PT - supply No. 88209 electromagnetic valve, ball valve and brass fitting

Technical Specification:

- Operating voltage: 24V DC
- Power input: 6,5 W

Shower Control without Piezo Button with Flowmeter



SLZA 20K



SLZA 20KH



SLZA 20KT

Characteristics:

- only for use with set of SLZA 02M
- SLZA 20K - destined for premixed water
- SLZA 20KH - destined for hot and cold water, temperature regulation by mixer
- SLZA 20KT - destined for hot and cold water, temperature regulation by thermostatic mixer
- after paying the amount into coin machine and adjusted time delay water starts to flow from shower head
- shower time can not be interrupted
- including the measurement of water flow, necessary to use SLZA 16
- material stainless steel AISI 304, brushed, material stainless steel AISI 316L could be made to order

Supply Specification:

- SLZA 20K - supply No. 89201 stainless steel cover with fitting
- SLZA 20KH - supply No. 89202 and electromagnetic valve,
- SLZA 20KT - supply No. 89203 ball valve and brass fittings

Technical Specification:

- Operating voltage: 24V DC
- Power input: 6,5 W